

Common Rail Diesel Additive

Ref 1072

12x500ml

USE

Bardahl Common Rail Diesel Additive has been developed for drivers who care about servicing their car.

It is a preventive additive that can be used during the whole engine lifespan.

Its use is recommended to prevent the common rail system from damage and wear.

Suitable for any type of diesel engine.

PROPERTIES

Bardahl Common Rail Diesel Additive has the following properties:

- Lubricates the upper part of cylinders and rings, and makes up for the sulphur absorption into diesel.
- · Protects valves and seats against
- Contains cetane booster for better engine performance.
- Disperses water from fuel.
- Contains antifreeze agents.
- Makes engine cold starting easier.
- Limits fuel overconsumption.
- Protects and keeps the fuel system clean.
- Reduces exhaust fumes.

INSTRUCTIONS FOR USE

Pour the contents of the can into fuel tank before filling up.

Compatible with any high pressure injection system (HDI, CDI, TDC, DCI), DPF and catalytic converters.

1 can treats 60 liters of fuel.

PHYSICAL & CHEMICAL **PROPERTIES**

Color	Yellow
Physical state at 20°C	Liquid
Density	0,8 g/cm³ (20°C)
Flash point	> 60 °C
Viscosity, kinematic	< 20,5 mm²/s (40°C)

V08/2019

