



XTC-M 10w40



DESCRIPTION

BARDAHL XTC-M 10w40 is a new generation synthetic oil developed to ensure the best engine cleanliness. It has been formulated for 4-stroke motorbike engines with wet or dry clutch. Up to Euro 5 standard, with post-treatment system: air injection and/or catalytic converter.

SPECIFICATIONS

This product offers the following performance level:

API	SN and retro compatible with SM, SL, SJ, SH, SG, SF
JASO	MA2

PROPERTIES

- ✓ BARDAHL XTC-M 10w40 offers friction performance adapted for faster response of clutch commands.
- ✓ BARDAHL has selected the best hydrotreated synthetic bases for better stability, energy saving and performance.
- ✓ The BARDAHL performance additives used in this formula will guarantee anti-wear action superior to other traditional oils, as well as the highest level of shear resistance to protect moving parts and extend engine and gearbox lifespan.
- ✓ Very good stability.
- ✓ Anti-corrosion and anti-foam properties.
- ✓ Good dispersion and detergency properties.



TECHNICAL DATA

Colour		Amber
Density at 15°C – kg/l	ASTM D1298	0,861 (20°C)
Viscosity at 40°C – mm ² /s	ASTM D445	86,90
Viscosity at 100°C – mm ² /s	ASTM D445	13,60
Viscosity Index	ASTM D2270	166
MRV Viscosity at -30°C – mPa.s	ASTM D4684	22000
Pour point - °C	ASTM D97	-39
CCS -25°C – mPa.s	ASTM D5293	<7000
TBN – mgKOH/g	ASTM D2896	7
Flash point - °C	ASTM D92	>170

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer manual before use. Miscible in other synthetic 4T motorbike oils.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

35921	12x1L
35922	4x4L
35924	60L
35927	205L