



XTS 5W20

DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

APPLICATION

BARDAHL XTS 5w20 has been specially formulated for the lubrication of FORD EcoBoost petrol engines. It also applies to JAGUAR and LAND-ROVER petrol engines (excluding compressed V6 and V8).

SPECIFICATIONS

This product offers the following performance level:

API	SP/RC
ILSAC	GF-6A
GM	Dexos 1TM Gen 3 / 6094M
FORD	WSS-M2C945-A/B1 / WSS-M2C960-A1 / WSS-M2C948B
CHRYSLER	MS 6395
FIAT	9.55535-CR1

PROPERTIES

- ✓ Avoids fuel over-consumption,
- ✓ Offers a stable viscosity and a high Viscosity Index,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold start easier,
- ✓ Provides an excellent resistance against « shearing »,
- ✓ Contains anti-corrosion, anti-wear and anti-foam additives.



TECHNICAL DATA

Density at à 15°C	Kg/l	0,854
Viscosity at -35°C	mPa.s	4550
Viscosity at 40°C	mm ² /s	49,1
Viscosity at 100°C	mm ² /s	8,74
Viscosity Index		158
Flash point COC, °C	°C	226
Pour point, °C	°C	-36
TBN Alcalinity	mgKOH/g	7,4
Sulphated Ash contents	%	0,85

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36291	12 X 1 L
36293	3 X 5 L
36298	20 L
36297	205 L