



XTC 5W30

DESCRIPTION

High performance and universal synthetic motor oil for petrol and diesel engines (including engines equipped with a DPF). Suitable for any type of engine, turbo-charged or not.

APPLICATION

Bardahl XTC 5w30 has been developed according to the Mid S.A.P.S technology to obtain the best engine cleanliness. This universal engine oil is suitable for extended oil drain intervals. It offers an excellent protection at cold start and at any engine temperature. **Approved by Mercedes-Benz.**

SPECIFICATIONS

This product offers the following performance level:

ACEA	C3
API	SN
VW	502.00 / 505.00 / 505.01
MERCEDES-BENZ	MB Approval 229.52 / 229.51
FIAT	9.55535-S3
GM-OPEL	DEXOS 2
BMW	Longlife-04

PROPERTIES

- ✓ Avoids fuel overconsumption,
- ✓ Reduces the formation of combustion ashes,
- ✓ Forms a protective lubricating film at high temperature,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier,
- ✓ Provides an excellent resistance against shearing,
- ✓ Offers a high protection against corrosion, wear and the formation of foam.



NOTHING WILL STOP YOU

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahlois.com



TECHNICAL DATA

Density at 15°C	Kg/l	0,850
Viscosity at -30°C	mPa.s	6000
Viscosity at 40°C	mm ² /s	72,60
Viscosity at 100°C	mm ² /s	12,3
Viscosity Index		168
Flash point COC, °C	°C	230
Pour point, °C	°C	-36
TBN alcalinity	mgKOH/g	7,4
Sulphated ash contents	%	0,78

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36311	12 x 1 L
36312	4 x 4 L
36313	3 x 5 L
36318	20 L
36314	60 L
36317	205 L

