



# XTEC TRUCKS 10W30

## DESCRIPTION

Fuel Economy, synthetic oil made from the latest generation performance additives and formulated for diesel engines (trucks, busses and delivery vans) to reduce friction, eliminate sludge and optimize fuel consumption. It is based on the LOW SAPS (very low ash contents) technology to ensure an extended lifespan and a good functioning of post-treatment exhaust systems (DPF).

## APPLICATION

**Bardahl XTEC Trucks 10w30** provides an excellent stability and a high resistance to temperatures to avoid the formation of deposits, and makes cold start easier. Suitable for EURO III to EURO VI (with SCR). ON ROAD and OFF-HIGHWAY application.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	E7, E9
API	CK-4
MB	228.31
RENAULT VI	RLD-4
DEUTZ	DQC III-10 LA
VOLVO	VDS-4.5
MACK	EOS-4.5
FORD	M2C171-F1
MTU	Type 2.1
CUMMINS	CES 20086
CAT	ECF-3
DETROIT DIESEL	DFS 93K222

## PROPERTIES

- ✓ Exceeds the standard requirements of low emissions,
- ✓ Helps to extend the lifespan of particle filters,
- ✓ Offers high detergency properties and avoids the formation of deposits,
- ✓ Provides strong dispersion properties,
- ✓ Is highly resistant against corrosion and oxidation,
- ✓ Decreases wear and avoids the formation of foam,
- ✓ Has a low ash contents.





## TECHNICAL DATA

Density at 15°C	Kg/l	0,870
Viscosity at -25°C	mPa.s	6510
Viscosity at 40°C	mm <sup>2</sup> /s	81,20
Viscosity at 100°C	mm <sup>2</sup> /s	12
Viscosity Index		142
Flash point COC, °C	°C	228
Pour point, °C	°C	-39
TBN alcalinity	mgKOH/g	10
Sulphated ash contents	%	1

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

33038	20 L
33034	60 L
33037	205 L



**NOTHING WILL STOP YOU**

SADAPS BARDAHL ADDITIVES & LUBRICANTS  
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2  
T: (+32) (0) 69 59 03 60

[www.bardahl.fr](http://www.bardahl.fr)  
[www.bardahlois.com](http://www.bardahlois.com)