

XTC TRUCKS 10W40

DESCRIPTION

Semi synthetic oil formulated for heavy diesel engines (trucks, busses and delivery vans) and compatible with Euro I to V engines. It enables to reduce friction and eliminate sludge. It offers excellent detergency properties and a good resistance to wear.

APPLICATION

Bardahl XTC Trucks 10w40 offers an excellent stability and a high resistance to temperature changes to avoid the formation of deposits in the engine and make cold start easier.

SPECIFICATIONS

This product offers the following performance level:

ACEA	E7 A3B4
API	CI-4
МВ	228.3/ 229.1
RENAULT VI	RLD-2
DEUTZ	DQC III-10
VOLVO	VDS-3
МАСК	EO-N
MTU	DDC Type2
CUMMINS	20076/ 20077/ 20078
GLOBAL	DHD-1
JASO	DH-1

PROPERTIES

- $\checkmark~$ Offers high detergent properties and avoids deposits,
- \checkmark Is highly resistant against corrosion and oxidation,
- ✓ Provides good anti wear and anti-foam properties.





TECHNICAL DATA

Density at 20°C	Kg/l	0,872
Viscosity at -25°C	mPa.s	<7000
Viscosity at 40°C	mm2/s	85
Viscosity at 100°C	mm2/s	14,6
Viscosity Index		160
Flash point COC, °C	°C	216
Pour point, °C	°C	-35
Sulphated ash contents	%	1,5

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

<u>Handling</u>: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

<u>Storage</u> : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36104	20 L
36105	60 L
36109	205 L



SADAPS BARDAHL ADDITIVES & LUBRICANTS Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2 T: (+32) (0) 69 59 03 60

www.bardahl.fr www.bardahloils.com