



XTC TRUCKS 10W30 SHPD

DESCRIPTION

Semi synthetic oil formulated for heavy diesel engines (trucks, busses and delivery vans) that reduces friction and eliminates sludge. Compatible with Euro IV to V engines. It offers excellent detergency properties and a good resistance to wear. Anti-bore polishing.

APPLICATION

Bardahl XTC Trucks 10w30 SHPD offers an excellent stability and a high resistance to temperature changes to avoid the formation of deposits in the engine and make cold start easier, even under the most difficult weather conditions. With its special additives, it can be used with fuels with a relatively high sulfur content. This will allow extended oil change intervals and prevent wear on the cylinders.

SPECIFICATIONS

This product offers the following performance level:

ACEA	E7
API	CI-4 / SH
MB	228.3
RENAULT VI	RLD-2
DEUTZ	DQC III-10
MTU	Type2
CUMMINS	CES 20077/ 20078
CAT	ECF-1-a/ECF-2
MAN	M 3275-1

PROPERTIES

- ✓ Offers high detergent properties and avoids deposits,
- ✓ Repels water,
- ✓ Offers high cylinders and segments protection,
- ✓ Is highly resistant against corrosion and oxidation,
- ✓ Provides good anti-wear and anti-foam properties.





TECHNICAL DATA

Density at 20°C	Kg/l	0,865
Viscosity at -25°C	mPa.s	6760
Viscosity at 40°C	mm ² /s	75,10
Viscosity at 100°C	mm ² /s	11,4
Viscosity Index		144
Flash point COC, °C	°C	216
Pour point, °C	°C	-36
Sulphated ash contents	%	11,1
TBN mgKOH/g	%	1,43

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

33048	20 L
33044	60 L
33047	205 L

