



Auto

→ Diesel additives

# BDC

Ref. 1260

12x1L

## USE

Bardahl Diesel Combustion is a complete preventive diesel treatment, offering at the same time an antifreeze protection.

It can be used for any type of diesel vehicle (passenger cars, vans, busses, trucks, agricultural equipment, marine engines, ...).

## PROPERTIES

Bardahl Diesel Combustion BDC has the following properties:

- Lubricates and protects the injection system.
- Prevents the formation of carbon deposits on valves and allows for a better spraying of fuel into the engine by cleaning the injector nozzles.
- Reduces the harmful exhaust emissions.
- Improves the cetane rate for a better combustion and a reduction of consumption.
- Repels condensation water and therefore prevents the formation of bacteria which can provoke severe damage to the fuel pump.
- Protects against corrosion (ASTM D665 test) and oxidation (ASTM D2274 test).
- Offers an antifreeze up to -27°C protection by lowering the Limit Filterability Temperature (LFT).

## INSTRUCTIONS FOR USE

Preventive use: from 0.5 to 1L of BDC for 1000L of diesel.

In the winter: 2L of BDC for 1000L of diesel. We advise you to treat your diesel before the outside temperature goes under +5°C.

Storage: above +5°C.

## PHYSICAL & CHEMICAL PROPERTIES

Colour	Orange / Brown
Physical state at 20°C	Liquid
Density	0,843 g/cm <sup>3</sup>
Flash point	62 °C
Viscosity, kinematic	< 20,5 mm <sup>2</sup> /s

