



XTM-M 2T

DESCRIPTION

BARDAHL XTC-M 2T is a performance 2-stroke mineral oil.

SPECIFICATIONS

This product offers the following performance level:

API	TC
JASO	FB

PROPERTIES

- ✓ Suitable for oil injector systems or premix. Mixing ratio: from 3% to 4%.
- ✓ BARDAHL has selected the best hydrotreated synthetic bases to ensure more stability, better performance and energy-saving.
- ✓ Limits carbon deposits.
- ✓ Excellent miscibility with fuel.

TECHNICAL DATA

Colour		Blue
Density at 15°C – kg/l	ASTM D1298	0,865 (20°C)
Viscosity at 40°C – mm²/s	ASTM D445	90,8
Viscosity at 100°C – mm²/s	ASTM D445	11,34
Viscosity Index	ASTM D2270	113
Pour point - °C	ASTM D97	-16
TBN – mgKOH/g	ASTM D2896	1
Flash point - °C	ASTM D92	>116

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.



RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer manual before use. Miscible with other 2-stroke motorbike oils.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

35791	12x1L
-------	-------