



→ Diesel additives



Diesel antifreeze

Ref. 2357B

24x125ml

USE

Do not increase the treatment dosage and treat fuel with Bardahl Diesel antifreeze before the temperature goes below +5°C.

Antifreeze protection depends on the quality of diesel fuel.

Can be used with any type of diesel fuel, even mixed with biodiesel.

PROPERTIES

- Protects the diesel fuel against freezing up to maximum -28°C
- Separates the paraffin crystals
- Prevents crystal binding
- Makes the engine cold starting easier
- Prevents the development of bacteria and prevents the clogging of the fuel filter
- Does not modify the cetane rate of diesel fuel
- Improves the fuel lubrication properties at cold temperatures

Bardahl Diesel antifreeze is safe for the complete fuel system (pump, injectors, common rail injection and exhaust catalysators).

INSTRUCTIONS FOR USE

1 can treats maximum 80 liter diesel fuel.

PHYSICAL & CHEMICAL PROPERTIES

Physical state	Liquid
Appearance	Clear
Color	Colorless

**NOTHING WILL STOP YOU**

SADAPS BARD AHL CORPORATION S.A.
Rue de Lille, 104. 59420 MOUVAUX
T: (+33) (0)3 10 38 38 38

SADAPS BARD AHL ADDITIVES & LUBRICANTS
Rue de Mont des Carliers, 3. ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr

V08/2019